LIFT MASTER BOOM, ECONOMY BOOM, NON-TELESCOPING-LM-EBNT-8-24 APPROX WEIGHT: 432.22 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!! *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 32' 24'' FORK 4 3/8" 80 3/8" POCKET VERTICAL CENTERS CENTER OF GRAVITY 11 1/2" 3" 0 0 21/40 ۲ 32 9/16" HORI7ONTAL CENTER OF GRAVITY 7 1/4" 16" *--MAXIMUM SINGLE HOOK CAPACITIES CENTER OF GRAVITY DISTANCE 36" 48" 60" 72" 78 1/2" CAPACITY 8000 6650 6000 5300 4850 DIMENSION TOLERANCE ± 1/4" I. THE UNDERSIGNED, AGREE THAT THE PRODUCT AS STANDARD FEATURES SPECIAL FEATURES REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO NONE Α MODEL NUMBER IS LM-EBNT-8-24 CONFIRM PRODUCT AND INSTALLATION Ρ CAPACITY IS 8.000 LBS. COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ WEIGHT / LOST LOAD IS 435 LBS AND LOCAL REGULATIONS AND STANDARDS. R **OVERALL WIDTH IS 32"** ANY MODIFIED UNITS ARE NON-RETURNABLE 0 FORK POCKET CENTERS IS 24" [] As drawn [] As marked V OVERALL LENGTH IS 80 3/8" Α Signed: Date: **OVERALL HEIGHT IS 11 1/2"** USABLE FORK POCKET IS 2 1/4" X 7 1/4" Printed Name: **36" MINIMUM HOOK POINT** LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING 78 1/2" MAXIMUM HOOK POINT DISTRIBUTOR'S NAME: P.O.# FOR INTERNAL USE ONLY Х **EFFECTIVE THICKNESS IS LESS THAN 1"** PROJECT SIGN OFF VESTIL MANUFACTURING W.O.# Х SALES SALES: X NEVER EXCEED LOAD CENTER RATING PER FORK DATE: 7/30/2015 DRAWN BY: **B.NOTHNAGEL** TRUCK MANUFACTURER'S GUIDELINES. ENG. SCALE: 1:16 FILE NAME: DO NOT USE THIS FORK TRUCK ATTACHEMENT REFERENCE: FAB. IF LOAD WILL EXCEED FORK TRUCK QUOTED LEAD TIME: ¥ QUOTE # 08-007-208 POWER MANUFACTURER'S LOAD CENTER RATING.

Х