
APPROX WEIGHT: 193.74 lbs.

WORK PLATFORM- WP-3648

\*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



## STANDARD FEATURES

## SPECIAL FEATURES

**POWER** 

**MODEL NUMBER IS WP-3648** CAPACITY IS 1,000 LBS. (EVENLY DISTRIBUTED LOAD) OVERALL WIDTH IS 36 3/16" **USABLE WIDTH IS 33 3/8" OVERALL LENGTH IS 51"** USABLE LENGTH IS 45 3/8" 42"HIGH HANDRAIL WITH 21" MIDRAIL AND 4 1/8" TOEBOARD SELF-CLOSING DOOR SWINGS IN ONLY (WILL NOT OPEN OUT) FORK LOCK IS ROTATED UP BEHIND BACK OF FORK AND LOCKED WITH SPRING LOADED PLUNGER 36" LONG STRAP WITH HOOK (NOT SHOWN) MUST ATTACH PLATFORM TO FORK TRUCK 60" HIGH EXPANDED MESH BACKING USABLE FORK POCKET HEIGHTS: 3 7/8" REAR, 1 7/8" FRONT **USABLE FORK POCKET WIDTH: 7 3/4"** MANUFACTURED TO MEET OUR INTERPRETATION OF OSHA STANDARDS TOUGH BAKED IN POWDER COATED ERGO BLUE FINISH

**NEVER EXCEED LOAD CENTER RATING** PER FORK TRUCK MANUFACTURER'S GUIDLINES. DO NOT USE THIS FORK TRUCK ATTACHMENT IF LOAD WILL EXCEED FORK TRUCK MANUFACTURER'S LOAD CENTER RATING.

## **DIMENSION TOLERANCE ± 1/4"**

I. THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.

## ANY MODIFIED UNITS ARE NON-RETURNABLE

14-007-002

[ ] As drawn [ ] As marked Signed:

**Printed Name:** 

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAME:

Χ

PROJECT SIGN OFF	VESTIL MANUFACTURING
SALES	VESTIL IVII (I NOT / CTORITY)

P

P

R

0

V

Α

W.O.# SALES SALES: X C.WOLF 08/31/06 ENG. SCALE: 1:28 FILE NAME: FAB.

QUOTED LEAD TIME: X QUOTF #