



Foot and Powered Portable Hydraulic Lift Table

- AC and DC power option available.
- 0.25" reinforced steel top and base.
- 2 rigid and 2 swivel steel wheel casters.
- Standard designs available in 2 sizes: 30" x 30" and 48" x 30"
- Available in 4 capacities: 3,000 4,000 5,000 and 6,000.
- Precision telescoping guide tubes.

Specs

- Capacity: 4000 lbs
- Table size: 30" x 30"
- Raised height: 44"
- Lowered height: 26"
- Caster: 6"
- Lift: 18"
- Weight(foot opp.): 423 lbs
- Weight(electric opp.): 474 lbs

THIS DRAWING IN ALL PARTICULARS IS WESCO INDUSTRIAL PRODUCTS INC. PROPERTY. ALL RIGHTS OF DESIGN, INVENTION OR USE OF ARE RESERVED.

REV.	ECN & DATE	APP	WESCO INDUSTRIAL PRODUCTS INC.										
			LANSDALE PENNA. 19446										
			PART NAME HT-3034-18		DRAWN:								
			TOLERANCE UNLESS OTHERWISE SPECIFIED		CHECKED:								
			FRACTION 3 PLACE DECIMAL 2 PLACE DECIMAL		APP. ENGR.								
			<table border="1" style="width: 100%;"> <tr> <td>± 1/64</td> <td>± .005</td> <td>± .01</td> </tr> <tr> <td>ANGULAR ± 1-1/2'</td> <td colspan="2">SHEET 1 OF 1</td> </tr> <tr> <td colspan="3" style="text-align: center;">BREAK ALL SHARP EDGES AND REMOVE ALL BURRS</td> </tr> </table>		± 1/64	± .005	± .01	ANGULAR ± 1-1/2'	SHEET 1 OF 1		BREAK ALL SHARP EDGES AND REMOVE ALL BURRS		
± 1/64	± .005	± .01											
ANGULAR ± 1-1/2'	SHEET 1 OF 1												
BREAK ALL SHARP EDGES AND REMOVE ALL BURRS													
			<table border="1" style="width: 100%;"> <tr> <td style="font-size: 24pt;">B- 496051</td> <td style="font-size: 12pt;">REV</td> </tr> </table>		B- 496051	REV							
B- 496051	REV												